Professional Series™ 21.0 Gross HP 540 CC

Bore 3.70 in. (94.0 mm) Stroke 3.06 in. (77.8 mm) Oil Capacity 48 fl. oz. (1.4 L)

3.54"

(89.81)

3.54"

(89.81)

BOTTOM


VIEW



6.82" 9.39" (238.51) 11.81" (299.97) END 7.16" (181.86)

Features:

- Dura-Bore™ cast iron cylinder sleeve for extended life
- Float carburetor for consistent easy starting
- Maintenance-free Magnetron® electronic ignition for quick, dependable starts
- Advanced Debris Management System with a dual seal, catridge-style air filter provides maximum protection and extends engine life
- Overhead valve design (OHV) for cooler operation and longer valve life
- Patented linear balancing system provides smoother performance
- Premium oil filter
- Platinum spark plugs for extended life
- Buyer protection package provides two-year consumer engine warranty



Model Type	Shipping Weight	Crankshaft	Crankshaft (P.T.O.) Extension	Dimension	Starter Position Bolt-On/Changeable	Ext. Oil Fill & Dipstick	Governor	Controls	Pulse Fuel Pump	Oil Pump with Filter	Choke-A-Matic®	Ground Wire Terminal	Fuel Tank (Quarts)	Top Governor Speed	Notes
 33M777															
											1	1			

2.87"

(72.85)

2.87

(72.85)

 $(8.89 \pm .007)$

4X Ø .350" ±.003

3.54" | 4.10"

(89.81) (104.04)

[■] Fuel tank omitted. ▼ Engine equipped with 12 Volt Gear Drive Starter and 9 Amp DC Alternator.